

---

# Stucco Siciliano

Technical Data Sheet

---

Decorative marble-effect stucco, spatula-applied, for interiors.

## Product Description

**Stucco Siciliano** is a decorative stucco based on calcium sulphate modified with acrylic resins, vegetable oils, and micronized pigments. It produces decorative surfaces that faithfully reproduce the appearance of marble stuccos found in historic palaces and ancient residences.

The product delivers a glossy, luminous finish with remarkable depth and three-dimensionality, making it ideal for creating prestigious interior environments with a timeless, elegant character.

## Fields of Application

Suitable for internal wall surfaces, wood, and plasterboard properly prepared to achieve a glossy marble decorative effect. Ideal for residential interiors, hotels, restaurants, retail spaces, and any environment where a high-end decorative finish is desired.

## Technical Specifications

<b>Appearance</b>	Thixotropic paste
<b>Color in container</b>	Green, Red, or Yellow
<b>Density Kg/Lt</b>	1.650 ± 0.05
<b>Supply viscosity 25°C</b>	Thixotropic
<b>Volumetric dry residue</b>	85 ± 2%
<b>Theoretical yield</b>	400 - 500 gr/m <sup>2</sup> per coat
<b>Dilution</b>	Water, maximum 1% if necessary
<b>Application method</b>	Steel spatula
<b>Drying 25°C</b>	12 - 18 hours
<b>Sandability</b>	12 hours
<b>Minimum recoating</b>	4 - 6 hours
<b>Operating temperature</b>	-5°C / +120°C
<b>Storage stability</b>	12 months
<b>Standard packaging</b>	20 kg

---

---

## Application Method

### Surface Preparation

To achieve a glossy and aesthetically refined finish, surfaces must be perfectly leveled, smooth, non-absorbent, and primed with ISOACRYL diluted maximum 1:3 with water.

### Application

On a previously prepared and thoroughly dry surface, spread Stucco Siciliano with a polished stainless steel trowel in one or more layers, until a smooth layer of uniform color is obtained.

After 12 hours from the last application, sand with fine sandpaper (1500 grit, automotive type), remove dust, and apply the product in thin spots spaced apart from each other.

Before the product dries completely (within 30 minutes), smooth and polish with the spatula, applying light pressure.

*Note: Even following the same application method, the product in use may appear different with more or less intense shading. This depends on the skill of the decorator.*

## Warnings and Advice

- Apply in favorable climatic conditions (+5°C / +35°C and maximum relative humidity 75%).
- The substrate must be sufficiently dry at the time of application.
- Do not apply on surfaces with rising damp or with the presence of efflorescence.
- In case of low temperatures and high humidity, extend the recoating times between coats.
- Poor quality substrates (degraded tempera and stucco) can cause bubbles or detachment.

## Storage

Store in rooms protected from frost and direct sunlight, between a minimum of +5°C and a maximum of +35°C.

---

Colorificio Atria S.R.L. — Contrada Camarro Formeca 91028 Partanna (Tp) Italy — [www.atria.it](http://www.atria.it)

(\*) This information, although believed to be reliable, must be considered indicative. The company reserves the right to change it without notice. It is the responsibility of the users to verify in advance the suitability of the product for the specific use.